



Wood Flooring & Tackstrip Adhesive

1. PRODUCT NAME

TEC® Wood Flooring & Tackstrip Adhesive (216)

2. MANUFACTURER

H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504-6451 U.S.A.
800.552.6225 Office
800.832.9023 Technical Support
800.952.2368 Fax
tecspecialty.com

3. DESCRIPTION

Wood Flooring & Tackstrip Adhesive is a fast-cure, modified silane gun-grade adhesive designed for basic wood subfloor construction practices as well as wood flooring repair, wood stair nosings, wood molding/baseboards and tackstrip attachment to concrete subfloors. It is also a general-purpose construction adhesive suitable for use in both interior and exterior applications.

Key Features and Benefits

- Fast curing with high bond strength
- For bonding tackstrip to concrete subfloors
- For bonding plywood to joists

Packaging

10.1 fl. oz. cartridge (0.30 L)

Product #15036314

Coverage

Typically 31 lineal feet/cartridge using a 1/4" bead.

Suitable Substrates

- Plywood to lumber framings
- Wood moldings and baseboards
- Polystyrene insulation board
- Insulation board
- Wood flooring
- Carpet tackstrip
- Fascia installation

Storage

Store inside at temperatures of 60°F to 100°F. Best to keep from freezing. If frozen, allow to thaw before use. Keep container tightly closed when not in use. Always store in an upright position.

Shelf Life

Maximum 1 year from date of manufacture in properly stored, unopened container.

Limitations

- Temperature should be between 50°F and 100°F during installation.
- Do not use on wet, dusty or contaminated surfaces.

Cautions

Read complete cautionary information printed on product container prior to use. For medical emergency information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the covered TEC brand product(s) under normal environmental and working conditions. Because each project is different, H.B. Fuller Construction Products Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

4. TECHNICAL DATA

Physical Properties

TEC Wood Flooring & Tackstrip Adhesive (216)	
Description	
Base	Modified Silane
Physical State	Paste
Color	White
Open Time	15-20 minutes
Cure Time	45-75 minutes
VOC/Liter of Material	12 g/L

5. INSTALLATION INSTRUCTIONS

Application

Cut tip and puncture inner seal. Apply a serpentine bead of adhesive to the properly prepared substrate. Only apply as much adhesive as can be installed within 15-20 minutes under normal temperature and humidity conditions. Set time may be accelerated by a light misting of water over the extruded adhesive prior to installing materials to be bonded. (Do not puddle water.) IMMEDIATELY clean any adhesive smudges from the flooring material's surface with mineral spirits while the adhesive is still fresh/wet.

It is the sole responsibility of the installer to determine the suitability and compatibility of the adhesive for the intended application.

Clean-up

Use acetone or mineral spirits while wet. Use plastic scraper and terry cloth when dry.

6. AVAILABILITY

TEC premium surface preparation, tile, stone, carpet, wood and resilient floor covering installation products are available nationwide. To locate TEC products in your area, please contact:

Phone: 800-832-9002

Website: tecspecialty.com

7. LIMITED WARRANTY

The product(s) covered by this Product Data Sheet are sold subject to a Limited Warranty and related terms. **H.B. Fuller Construction Products disclaims the implied warranties of merchantability and fitness for a particular purpose and all incidental and consequential damages arising out of the sale, purchase or use of this product.** For Limited Warranty details visit tecspecialty.com. To obtain a hard copy of the Limited Warranty call H.B. Fuller Construction Products at 800-832-9023 or mail a written request to the address in Section 2 of this Product Data Sheet.

8. MAINTENANCE

Not applicable

9. TECHNICAL SERVICES

Technical and safety literature

To acquire technical and safety literature, please visit our website at tecspecialty.com.

10. FILING SYSTEM

Division 9



To learn more, visit TECspecialty.com



H.B. Fuller Construction Products Inc. | 1105 South Frontenac Street Aurora, IL 60504-6451



@TECInstallationSystems



tecspecialty.com



TECInstallationSystems



TEC Installation Systems